SL111 Series sirius[®] lighting CRIS Pendants

Specifications/Features

Sirius Lighting

Fixture

Fixture is milled from solid brass and finished in hand-polished chrome or platinum. Crystal glass is available in clear exterior finish with vacuum metallized reflector. Created exclusively for Sirius Lighting, these glass shades are for use only with CRIS pendant fixtures and are not compatable with any other fixture. Glass element must be ordered separately.

The reflector is made of aluminum coating. Some back light shows through the aluminum reflector.

Stem fixture measures 39-3/4" long, including glass.

String fixture measures 41-15/16" long, including glass; length is field adjustable.

Mounting

Three different mounting options allow for unlimited placement possibilities in lighting design:

- **SL:** Standard rail mount. Allows the fixture to be conveniently mounted anywhere along the rail system up to the maximum capacity of the circuit.
- **SP:** Mono-point pendant canopy for remote transformer.
- **SPT:** Mono-point pendant canopy with a built-in 60W 120/12V electronic transformer.

Lamp/Electrical

(1) 50W max. low pressure T4 axial filament lamp, GY6.35 base; or LED compatible lamp (by others). Rated for 12 or 24 volts.

Labels/Usage

CSA/us Listed

Ordering Information

Electronic Transformer

Example Order:	SL 11100S -	- PL SL904	46-CRIS
Mounting	Fixture	Finish	Glass
		-	
SL - Rail Mounted Fixt	tures 11100 - 39-3/4" L St	tem Pendant C - Polished Ch	rome SL9046-CRIS
SP - Pendant Canopy Remote Transfor	=======================================		
SPT - Pendant Canopy Built-In Step-Dow 120/12V 60W	with		

Catalog No.		
C		
Туре		
.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		

Project _

L9046-CRIS

